

AUDREY A7-1 LARGE & STYLISH 21.5" ALL-IN-ONE POS TERMINAL



As part of the Audrey Family by Partner Tech the Audrey A7-1 with its 21.5 inch display represents the largest All-in-one Terminal ever built by Partner Tech. It stands for Partner Tech's future vision of the POS with stylish features, innovative design with a wide screen display. A technologically rich solution that offers industrial grade performance with a high-quality design that will make a dramatic statement in your store's environment or hospitality area. Completely fanless with various processors to choose, advanced and fast memory and storage options, and 5 years of warranty the Audrey A7-1 is a future proof POS Terminal for many years to come. The terminal supports up to three displays running simultaneously which means that next to the standard second customer display a third monitor for digital signage can be connected via the HDMI port. Furthermore this All-in-one Terminal with its VESA mounting options can be placed on a pole or against a wall to use it as Panel PC. With the optional PS-104 stand you can transform the A7 into a kiosk with the display in portrait mode, an integrated printer and many more peripherals. The combination of performance in a large and stylish design differentiates the Audrey A7-1 from traditional POS solutions offered in the market today.

SPECIAL FEATURES

All-in-one POS with 21.5" TFT-LCD 10-point PCAP touch Up to 7th Generation Intel® Core™ i5 (Kaby Lake) High performance CPU Fanless Design High speed storage with M.2 PCIe Gen3.0 SSD DDR4 RAM up to 32 GB Support up to 3 independent displays (Operation, Customer and Digital Signage) Slim and stylish design for retail and hospitality

OPTIONAL

Windows POSReady 7 - only with Intel Bay Trail and Skylake CPU Linux (Ubuntu) PS-103 printer stand with Powered USB Hub Kiosk mode with PS-104 stand Multi-reader with MSR, IC Card Reader, Fingerprint, RFID, i-Button 2 x 20 VFD 10.1" Customer Display / optional with touch

TECHNICAL DATA



AUDREY A7-1

| MODELL | | AUDREY A7-1 | | | |
|-------------------|--------------------|--|---|--|--|
| | Max | 1920 x 1 | 080 | | |
| | Resolution | 1720 X 1 | | | |
| | Size | 21.5" | | | |
| | Brightness | 300 nits | | | |
| Display | Contrast | 1000:1 | | | |
| | Response Time | 22 ms typ | | | |
| | Supported Color | 16.7M | | | |
| | Viewing Angle | Right 89° Left 89° / Upper 89° Lower 89° | | | |
| | Tech- nology | TFT-LCD with LED backlight | | | |
| System | Touch | 10-point PC/ | oint PCAP touch | | |
| | CPU (fanless) | POS Ready 7, Windows 10 IoT, Linux (Ubuntu) Intel® Celeron® J1900 (Bay Trail) 2.00 GHz up to 2.40 GHz, Quad Core Intel® Celeron® 3955U (Skylake), 2.00 GHz, Dual Core Intel® Core™ i3-6100U (Skylake), 2.30 GHz, Dual Core Intel® Core™ i5-6300U (Skylake), 2.40 GHz up to 3.00 GHz, Dual Core Windows 10 IoT (64Bit), Linux (Ubuntu) Intel® Celeron® J3455 (Apollo Lake) 1.50 GHz up to 2.30 GHz, Quad Core Intel® Celeron® 3965U (Kaby Lake), 2.20 GHz, Dual Core Intel® Core™ i3-7100U (Kaby Lake), 2.40 GHz, Dual Core | | | |
| | | Intel® Core™ i5-7300U (Kaby Lake), 2 | | | |
| | Memory | Apollo Lake & Bay Trail: 4GB, 8GB DDR3L | | | |
| | | Skylake & Kaby Lake: 4GB, 8GB, 16GB DDR4 | | | |
| | Storage | Apollo Lake & Bay Trail: 128GB / 256GB M.2 SATA SSD Skylake & Kaby Lake: 128GB / 256GB M.2 PCIe Gen3.0 x2 SSD | | | |
| I/O Interface | | Apollo Lake, Skylake & Kaby Lake 2 x Serial ports, RS232 (RJ45), 0V/5V/12V selection by BIOS (COM1, COM2) 2 x RJ45, IEEE 802.3 10/100/1000 Mbps Ethernet 4 x USB 3.0 1 x RJ11 Cash Drawer (for 2 cash drawers) 1 x DC 12 V input power-jack 1 x DC 12 V out 1 x Line-out 1 x HDMI 1 x VGA | Bay Trail 3 x COM RS232 (RJ-45), OV/5V/12V selection by BIOS (COM1, COM2, COM3) 1 x RJ-45 Ethernet 1 x USB 3.0 & 3 x USB 2.0 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 x DC 12 V input power-jack 1 x DC 12 V input power-jack 1 x DC+12V Out 1 x Audio Line-out 1 x HDMI 1 x VGA | | |
| Expansion Slot | Internal | 1 x Mini-PCle | | | |
| Speaker | Power | 1 x 3 Watts | | | |

TECHNICAL DATA



AUDREY A7-1

| MODELL | | AUDREY A7-1 | | | |
|---------------------------|-------------------------|--|--|---|--|
| Ontional | Expansion I/O | Bay Trail: A) 1 x COM + 1 LPT B) 1 x 12V + 1 x 24V Powe- red USB | Apollo Lake: A) 2 x COM B) 1 x COM + 1 x LPT C) 1 x 12V + 1 x 24V Powered USB | Skylake & Kaby Lake: A) 2 x COM Port B) 1 x COM + 1 x LPT Port C) 1 x COM + 2 x USB 3.0 D) 2 x USB 3.0 + 1 x 12V + 1 x 24V Powered USB | |
| Optional Configuration | Attached Peripherals | PS-103 printer stand with Powered USB Hub Kiosk mode with PS-104 stand Multi-reader with MSR and IC Card Reader and (Fingerprint or RFID or i-Button) 10.1" Customer Display CD-101C / optional with touch 2 x 20 VFD Apollo Lake, Skylake and Kaby Lake CPUs support up to 3 independent displays (Operation, Customer and Digital Signage) | | | |
| Others | Management | Intel AMT and Intel V-Pro (Only support for i5 CPU) | | | |
| | Colors | Black + Silver Grey; Rose Gold + Silver | | | |
| | VESA Mount. | 75 x 75 | | | |
| | Material | Aluminum stand and back, plastic frame | | | |
| | Certifications | CB, EMC (CE, FCC, VCCI, BSMI), BSMI | | | |
| Power | Power Adapter | AC-In 100~240V / DC-Out 12 V, 90 W | | | |
| Dimensions | w/o stand | 531(W) x 339 (H) x 45.7 (16.5) (D) mm | | | |
| | with stand | 531(W) x 390 (H) x 200 (D) mm | | | |
| Tomporaturo | Operating | | 5°C ~ 40°C | | |
| Temperature | Storage | -15°C ~ 60°C | | | |
| Humidity | Operating | 15% ~ 80% | | | |
| | Storage | 15% ~ 80% | | | |

*Specifcation is subject of change without prior notice.



PARIIINER CARE . TRUST . RESPONSIBILITY

EUROPE UNITED KINGDOM IBERIA ADRIA

+34 913 120632 +38615662520

+49 40 450 635-0 info@partner-tech.eu +44 1928 579 707 sales-uk@partner-tech.eu comercial@partner-tech.eu prodaja@partner-tech.eu

| | 2019 |
|--|---------------------------------|
| | Feb 2 |
| | ons |
| | erati |
| | o alt |
| | ect t |
| | Subject to alterations Feb 2019 |